



LVT Silent PUR SLIDE 1,4 mm

+Für schwimmend verlegte LVT-Click-Bodenbeläge.

+Gleitfähige SLIDE-Oberfläche.

+Für stark frequentierte Räume und den Einsatz im Objektbereich.

- Dauerelastische, alterungsbeständige Polyurethan-Schwermatte aus 90% natürlichen Rohstoffen, PU-Bindemittel und mineralischen Füllstoffen.
- LVT-Belag liegt schwimmend auf der Unterlagsbahn.
- Erleichtert die Verriegelung je nach Hersteller und Art der Verriegelung.
- Hohes Rückstellvermögen.

LVT Silent PUR SLIDE 1.4 mm

+For floating LVT click floor coverings.

+Low-friction SLIDE-surface

+For high traffic areas and for application in commercial properties.

- Permanently elastic, non-ageing polyurethane underlay from 90% natural materials, PU-bonding agent and with mineral fillers.
- LVT flooring lies floatingly on the underlay.
- Facilitates the locking depending on the manufacturer and type of locking.
- High resilience.

Technische Daten

Trittschallreduzierung	[IS]	●●○○○	15 dB(A)	Impact Sound
Gehschallreduzierung	[RWS]	●●●●●	22 %	Reflected Walking Sound
Wärmedurchlasswiderstand	[R]	○○○○○	0,01 m² K/W	Thermal Resistance
Eignung auf Fußbodenheizung		●●●●●	ja / yes	Suitable on underfloor heating
Punktuellder Ausgleich	[PC]	●●○○○	0,59 mm	Punktual Conformability
Feuchteschutz	[SD]	○○○○○		Moisture protection
Druckbeanspruchung	[CS]	●●●●●	440 kPa	Compressive Strenght
Dynamische Beanspruchung	[DL]	●●●●●	2.000.000 Zyklen	Dynamic Load
Dauerhafte Druckbeanspruchung	[CC]	●●●●●	94 kPa	Compressive Creep
Stoßbeanspruchung	[RLB]	●●●○○	600 mm	Resistance to Large Ball
Gleitfähige Oberfläche		●●●●●		Low-friction surface

Technical data

Impact Sound
Reflected Walking Sound
Thermal Resistance
Suitable on underfloor heating
Punktual Conformability
Moisture protection
Compressive Strenght
Dynamic Load
Compressive Creep
Resistance to Large Ball
Low-friction surface



Frei von Formaldehyd
und flüchtigen organi-
schen Verbindungen.
Free of formaldehyde
and volatile organic
compounds.

