



Übergangsprofil Nr. 130, 30 mm

- Aluminium.
- Mittig versenkt gelocht.

| | |
|----------------------|---------------------------|
| Werkstoff: | EN AW 6063 (DIN EN 573) |
| Werkstoffzustand: | T6 (DIN EN 755-2) |
| Vorbehandlung: | E6 (DIN EN 17 611) |
| Schichtdicke Eloxal: | Klasse 15 (DIN EN 17 611) |

| | |
|----------------------|---|
| Zubehör: | Befestigungsmaterial, farblich passend. |
| Geeignet für: | Textile und elastische Bodenbeläge |
| Montageart: | Schrauben |
| Längen: | 500, 270, 100, 90 cm |
| Farben: | gold, sahara, silber, bronze, Edelstahl matt, Edelstahl gebürstet |

Übergangsprofile schaffen Übergänge zwischen nahezu beliebigen, gleichhohen Bodenbelägen.

Die in verschiedensten Breiten, Formen, Materialien und Farben erhältlichen Profile lassen sich schnell und unkompliziert verlegen.

Connection section no. 130, 30 mm

- Aluminium.
- Centre countersunk holes.

| | |
|------------------------------|--------------------------|
| Material: | EN AW 6063 (DIN EN 573) |
| Material condition: | T6 (DIN EN 755-2) |
| Pre-treatment: | E6 (DIN EN 17 611) |
| Thickness of anodised layer: | Class 15 (DIN EN 17 611) |

| | |
|----------------------|---|
| Accessories: | Fastening material in matching colors. |
| Suitable for: | Textile and elastic floor coverings |
| Installation: | screwing |
| Lengths: | 500, 270, 100, 90 cm |
| Colours: | gold, sahara, silver, bronze, stainless steel matt, stainless steel brushed |

Connection sections create transitions between almost any level of flooring.

The profiles are available in a wide range of shapes, materials and colors and can be laid quickly and easily.