



SPC Silent PUR 1,2 mm

+Für die schwimmende Verlegung von Rigid-Core-Belägen der Kategorie SPC.

+Sehr hohe Druckbeanspruchung zur Entlastung des Verriegelungssystems.

+Für stark frequentierte Räume und den Einsatz im Objektbereich.

+Für maximale dynamische Beanspruchungen geeignet.

- Dauerelastische, alterungsbeständige Polyurethan-Schwermatte aus 90% natürlichen Rohstoffen, PU-Bindemittel und mineralischen Füllstoffen.
- Hohes Rückstellvermögen.

SPC Silent PUR 1.2 mm

+For the floating installation of rigid core-floorings categorized as SPC.

+Very high compressive strength to relieve the locking system.

+For high traffic areas and for application in commercial properties.

+Suitable for maximum dynamic loads.

- Permanently elastic, non-ageing polyurethane underlay from 90% natural materials, PU-bonding agent and with mineral fillers.
- High resilience.

Technische Daten

Trittschallreduzierung	[IS]	●●○○○	16 dB(A)	Impact Sound
Gehschallreduzierung	[RWS]	belagabhängig / flooring dependent		Reflected Walking Sound
Wärmedurchlasswiderstand	[R]	○○○○○	0,01 m² K/W	Thermal Resistance
Eignung auf Fußbodenheizung		●●●●●	ja / yes	Suitable on underfloor heating
Punktuellder Ausgleich	[PC]	●○○○○	0,22 mm	Punktual Conformability
Feuchteschutz	[SD]	○○○○○		Moisture protection
Druckbeanspruchung	[CS]	●●●●●	550 kPa	Compressive Strenght
Dynamische Beanspruchung	[DL]	●●●●●	3.000.000 Zyklen	Dynamic Load
Dauerhafte Druckbeanspruchung	[CC]	●●●●●	100 kPa	Compressive Creep
Stoßbeanspruchung	[RLB]	●●●○○	550 mm	Resistance to Large Ball

Technical data

Impact Sound
Reflected Walking Sound
Thermal Resistance
Suitable on underfloor heating
Punktual Conformability
Moisture protection
Compressive Strenght
Dynamic Load
Compressive Creep
Resistance to Large Ball



Frei von Formaldehyd und flüchtigen organischen Verbindungen.
Free of formaldehyde and volatile organic compounds.



Ökologisch
unbedenklich
Ecologically
safe

